



CARBON BLOCK FILTER CARTRIDGES

Activated carbon block cartridges, for the removal of chlorine, sediment, and volatile organic compounds in water. High absorption and capacity. Exceptional cost-to-performance value. Good flow rates at low pressure drop. NSF/ANSI standard 42 certified, for material requirements only. Standard dimensions – sizes to fit all common filter housings.



Model Number	Dimensions	Micron	Chlorine Capacity @ Flow	Temperature Range	Maximum Operating Pressure	Case Pack	Filtration Material	Quality Standard
20CB-251005	2.5x9-3/4	5	>4,000 gallons @ 1 GPM	50° F – 125° F	250 psi	20	Coconut Shell	NSF/ANSI Standard 42 for Material requirements only
20CB-252005	2.5x20	5	>8,000 gallons @ 1 GPM	50° F – 125° F	250 psi	12	Coconut Shell	
20CB-451005	4.5x10	5	>10,000 gallons @ 1 GPM	50° F – 125° F	250 psi	12	Coconut Shell	
20CB-452005	4.5x20	5	>20,000 gallons @ 1 GPM	50° F – 125° F	250 psi	6	Coconut Shell	

NOTE:

Performance capacity depends on the system design, flow rate, and certain other application conditions. Chlorine capacity @ flow, micron rating, maximum pressure are tested by manufacturer and independent laboratory.

WARNING:

Do not use with microbiologically unsafe or unknown water quality without adequate disinfection before or after the system.

Southeast (FL)
T 904-425-8023
F 904-425-8024
jireland@ewp-usa.com

Warehouse:
Jacksonville, FL
sales@ewp-usa.com

Northeast (MD)
T 443-451-5056
F 443-451-4378
jarmon@ewp-usa.com