

MANUAL SOFTENER VALVES

TFM64A 1" manual softener valve

Certificates: CE, RoHS

Technical Parameters:

Operating pressure: 15 psi – 90 psi
Water temperature: 40°F – 115°F
Water capacity: 20 gpm
Tank diameters: 6" – 18"
Tank connection: 2.5"
Inlet/outlet: 1" FNPT
Drain: 1/2" FNPT
Brine connection: 3/8" MNPT
Riser tube: 1.05"



TFM64D 2" manual softener valve

Certificates: CE, RoHS

Technical Parameters:

Operating pressure: 15 psi – 90 psi
Water temperature: 40°F – 115°F
Water capacity: 44 gpm
Tank diameters: 10" – 30"
Tank connection: 4"
Inlet/outlet: 2" FNPT
Drain: 1" FNPT
Brine connection: 1/2" MNPT
Riser tube: 1.50"
Side mount adapter available

Features:

1. Manual filter valves utilize the latest technology ceramic, corrosion proof, excellent sealing, and long service life.
2. Manual regeneration when needed.
3. Ejection nozzle self cleans to prevent blockage.
4. Feed water is automatically shut off during regeneration.
5. Can also be used as a filter valve.

Applications:

1. Household water softening.
2. Boiler water softening.
3. RO pretreatment.
4. Swimming pools.
5. Ion exchange equipment.

Southeast (FL)**T 904-425-8023****F 904-425-8024****jireland@ewp-usa.com****Warehouse:****Jacksonville, FL****sales@ewp-usa.com****Northeast (MD)****T 443-451-5056****F 443-451-4378****jarmon@ewp-usa.com**